Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: LEDVANCE | |
|---|--|
|---|--|

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC33456

| Τv | pe | of | light | source | : |
|-----|----|----|-------|--------|---|
| - 7 | ~ | • | | | • |


| Lighting technology used: | LED | Non-directional or directional: | NDLS | |
|-------------------------------|---------------|---------------------------------|------|--|
| Light source cap-type | Constant cur- | | | |
| (or other electric interface) | rent: 88 mA | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | No | |
| Product parameters | | | | |

Product parameters

| | | 1 Todact parar | | |
|---|---|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | arameters: | |
| 0, | nption in on- 00 h), rounded st integer | 8 | Energy efficiency class | D |
| dicating if it refe a sphere (360º) | s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º) | 850 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode power (P _{on}), expressed in W | | 7,1 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 1 | Spectral power dis- | See image |
| sions without | Width | 7 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 568 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | |
|--|------|------------------------------|-------|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | |
| | | Chromaticity coordi- | 0,382 | |
| | | nates (x and y) | 0,380 | |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | |
| the lumen maintenance factor | 0,96 | | | |

(a)'-': not applicable; (b)'-': not applicable;



Model placed on the Union market from 09/09/2021



EPREL registration number: 617543 https://eprel.ec.europa.eu/qr/617543

Supplier: LEDVANCE GmbH (Manufacturer) Website: http://www.ledvance.com/

Customer care service:

Name: LEDVANCE GmbH Website:

Email: contact@ledvance.com Phone: +49 89-780673-100

Address:

Parkring 33, Garching, Germany